



NUSTRI

MADE IN ITALY



Ironing machines for knitwear factories, laundries and clothes factories



 **MOD. 340/A**


Air operated press ideal for the iron of **trousers**. Steaming , heated upper surface. Vacuum and steaming lower surface. Complete of electric-vacuum and arranged for the connection with central source of steam and air.



Ironing machines for knitwear factories, laundries and clothes factories

TECHNICALS CHARACTERISTICS	MOD.	340/A
UPPER SURFACE	-	STEAMING
LOWER SURFACE	-	STEAMING
UPPER SURFACE HEATING	-	BY STEAM
LOWER SURFACE HEATING	-	BY STEAM
VACUUM	Kwatt.	0.4
VACUUM DISCHARGE PIPE	Ø	100 mm
AIR PRESSURE	bar	7
COMPRESSED AIR FEED	Ø	3/8"
STEAM FEED	Ø	1/2"
STEAM PRESSURE	bar	5
STEAM CONSUMPTION	kg/h	18 - 20
CONDENSATE INLET	Ø	1/2"
ELECTRIC FEED	Volts.	230/400 *
TENSION	Hz.	50 *
DIMENSIONS H x L x D	Cm.	170 x 125 x 120
NET WEIGHT	Kg.	310
* Different technicals characteristics are available on demand.		

Surface dimensions



Complete of

- ◆ Foot-board and safety frame for upper surface
- ◆ Steam heated upper surface
- ◆ Vacuum and steaming lower surface
- ◆ Stuffed lower and upper surface
- ◆ Electric vacuum
- ◆ Pneumatic suctioning valve
- ◆ Pressure regulator
- ◆ Steaming timer
- ◆ Suctioning timer
- ◆ Upper surface lock timer
- ◆ Arranged for the connection to centralized source of air and steam

Encombrance

